

GRAVELY *Technical* **BULLETIN**



BULLETIN NO. 1141

DATE: FEBRUARY 4, 1965

TO: ALL OUTLETS

SUBJECT: REVISION IN SUPER HOOD

A new design for the Super Hood has been completed and the factory is now shipping the new hoods. The change will enable the user to service the Super Tractor by lifting the hood from the front, as well as the back. This arrangement will only be available on tractors equipped with the new starter bracket that has the newly designed tension clip and special rod.

The new starter kits are available, but we would recommend that the dealers relieve their inventory of the old style starter kits before they go to the new. The problem of having an odd quantity of Super Hoods will, in some cases, necessitate the dealer using the new style SUPER HOOD with the old style battery bracket.

The use of the NEW SUPER HOOD with the old style battery bracket is possible by redrilling the hoods to use the Starter Hood pivot hinge.

Instructions for conversion are as follows: (Refer to Attached Sketch)

- A. Drill two 7/32" holes on each side of the hood.
1. Locate on a center line 1 3/8" from front of hood.
 2. Bottom hole 3/8" from bottom of hood to center of hole.
 3. Top hole is DIRECTLY ABOVE the bottom hole, 3/4" to center of hole or 1 1/8" from bottom of hood.

This modification work will only be a temporary operation since most will work out of the old style starter brackets or kits.

REVISION OF SUPER HOOD
Reference to Bulletin 1141

